



| | | | | | |
|----------------|-----|---|-------------------------------|--|--|
| 1 | | | | | |
| M810-Canopen01 | 2.0 | 5 | kg-cm/(0.2N) | | |
| 2 | | | | | |
| B | ms | | kg-cm/(6.081 b-i n)/(0.68N) | | |
| C | | | | | |
| D | M# | | 15kg-cm/(13.01 b-i n)/(1.47N) | | |

3 PDO

M810-Canopen 4 TxPDO 4 RxPDO PDO 4 16bit
 PDO "M800_Canopen.eds"
 RxPDO

| | | | | |
|---------|------|--|-------------------------------|---------|
| / | | | | |
| 6040h/0 | | Bit 0: 0 1 Bit 1: 0 1 Bit 2: 0 1 Bit 3: 0 1 Bit 4: 0 1 Bit 5: 0 1 Bit 6: 0 1 Bit 7: 0 1 | | |
| 2100h/0 | | : 0.1% | 0.0 300.0% | 0 3000 |
| 2101h/0 | | : 0.1% | 0.0 300.0% | |
| 2102h/0 | | : 0.01Hz | 0.00 599.00Hz | 0 59900 |
| 2103h/0 | | : 0.01Hz | 0.00 599.00Hz | |
| 2104h/0 | VF | : 1V | 0 1000V | |
| 2105h/0 | DO | Bit 0 DO1 0 1 Bit 1 DO2 0 1 Bit 2 DO3 0 1 Bit 3 RO 0 1 | | |
| 2106h/0 | A01 | : 0.01% | 0.00 100.00% | 0 10000 |
| 2107h/0 | H001 | : 0.001kHz | 0.000 50.000kHz 0 50000 | |
| 2108h/0 | H002 | : 0.001kHz | 0.000 50.000kHz | |
| 2109h/0 | PI D | : 0.1% | -100.0 100.0% (-1000 1000) | |
| 210Ah/0 | PI D | : 0.1% | -100.0 100.0% | |
| 210Bh/0 | | | | |
| 210Ch/0 | | : 0.1% | -300.0 300.0% | |
| 210Dh/0 | | : 0.01Hz | 0.00 599.00Hz | |

TxPDO

| | | | | |
|---|--|--|--|--|
| / | | | | |
|---|--|--|--|--|

| | | | | |
|---------|------|---|-----------------------------|---------|
| 6041h/0 | | Bit 0: 0 1 Bit 1: 0 1 Bit 2: 0 1 Bit 3: 0 1 Bit 4: 0 1 Bit 5: 0 1 Bit 6: 0 1 1 2 Bit 7: 0 1 Bit 8: 0 1 Bit 9 Bit 10: 0 1 2 | | |
| 2200h/0 | | : 0.1A | 0.0 6553.5A | 0 65535 |
| 2201h/0 | | : 1V | 0 65535V | |
| 2202h/0 | | : 0.01Hz | 0.00 599.00Hz | 0 59900 |
| 2203h/0 | | : 0.1% | -300.0 300.0% -3000 3000 | |
| 2204h/0 | | : 0.1V | 0.0 6553.5V | |
| 2205h/0 | DI 1 | Bit 0 DI 1 0 1 Bit 1 DI 2 0 1 Bit 2 DI 3 0 1 Bit 3 DI 4 0 1 Bit 4 DI 5 0 1 | | |
| 2206h/0 | DI 2 | Bit 1 DI 6 0 1 Bit 2 DI 7 0 1 Bit 3 DI 8 0 1 | | |
| 2207h/0 | DO | Bit 0 DO1 0 1 Bit 1 DO2 0 1 Bit 2 DO3 0 1 Bit 3 RO 0 1 | | |
| 2208h/0 | | | | |

